

CLAIM LISTING

1. (Currently amended) A system for providing wireless communication services to a plurality of wireless subscriber devices that are located in an aircraft, comprising:

aircraft network means located in said aircraft for generating radio frequency communication signals to communicate with at least one of said plurality of wireless subscriber devices that are located in said aircraft;

air-to-ground network means for radio frequency communications between said aircraft and a ground-based communications network system having at least one transceiver located on the ground; and

aircraft interface means for interconnecting said aircraft network means and said air-to-ground network means to establish communications between said plurality of wireless subscriber devices and said ground-based communications network by exchanging both subscriber traffic and at least one of network signaling and administrative data on separate concurrently available logical channels between said aircraft network means and said ground-based communications network.

2. (Original) The system for providing wireless communication services of claim 1 wherein said aircraft network means comprises:

aircraft cellular communication means for establishing at least one cell site to communicate via communications with at least one of said plurality of wireless subscriber devices.

3. (Original) The system for providing wireless communication services of claim 2 wherein said aircraft cellular communication means comprises:

at least one base station means, each of which establishes a cell site to communicate via communications with at least one of said plurality of wireless subscriber devices.

Serial No. 10/730,329

Amendment And Remarks Responsive To

Office Action Mailed 05/18/05

Page 2 of 32

219523v2

4. (Original) The system for providing wireless communication services of claim 3 wherein said aircraft interface means comprises:

authentication means for verifying the identity of said plurality of wireless subscriber devices.

5. (Original) The system for providing wireless communication services of claim 3 wherein said aircraft interface means comprises:

authorization means for determining a set of services that each of said plurality of wireless communication devices is authorized to receive.

6. (Original) The system for providing wireless communication services of claim 3 wherein said air-to-ground network means comprises:

wireless subscriber device means, connected to said at least one base station means and responsive to receipt of radio frequency communication signals from a one of said plurality of wireless subscriber devices, for emulating operation of said one wireless subscriber device in communicating with said ground-based communications system.

7. (Original) The system for providing wireless communication services of claim 3 wherein said air-to-ground network means comprises:

transmitter means for generating downlink radio frequency signals for transmission to said at least one transceiver located on the ground;

receiver means for receiving uplink radio frequency signals received from said at least one transceiver located on the ground; and

antenna means located on an external surface of said aircraft for exchanging said downlink and uplink radio frequency signals between said transmitter and said receiver means and said at least one transceiver located on the ground.

8. (Currently amended) The system for providing wireless communication services of claim 2 wherein said aircraft cellular communication means comprises:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 3 of 32

219523v2

a plurality of base station means to communicate via communications with at least one of said plurality of wireless subscriber devices, each at least one of said plurality of base station means operating in a cellular technology that differs from those of the remaining ones of said plurality of base station means.

9. (Original) The system for providing wireless communication services of claim 8 wherein said aircraft interface means comprises:

data concentrator means for converting the individual traffic and signaling channels received from said plurality of base station means to an aggregate data stream.

10. (Currently amended) The system for providing wireless communication services of claim 9 wherein said air-to-ground network means comprises:

ground station controller means for mobility management and hand over management for said aggregate data stream, comprising subscriber traffic from said plurality of wireless subscriber devices.

11. (Currently amended) The system for providing wireless communication services of claim 9 wherein said air-to-ground network means further comprises:

a plurality of ground-based base station means for communicating with at least one of said plurality of wireless subscriber devices; and

~~data router~~ disaggregator means for disaggregating said aggregate data stream by technology into a plurality of data streams and delivering each of said plurality of data streams to a corresponding one of said plurality of ground-based base station means.

12. (Original) The system for providing wireless communication services of claim 9 wherein said air-to-ground network means further comprises:

a plurality of mobile switching system means for interconnecting said communications from at least one of said plurality of wireless subscriber devices with conventional Voice and Data switching systems.

Serial No. 10/730,329

Amendment And Remarks Responsive To

Office Action Mailed 05/18/05

Page 4 of 32

219523v2

13. (Original) The system for providing wireless communication services of claim 1 wherein said aircraft network means comprises:

aircraft cellular communication means for establishing at least one wireless LAN-based cell site to communicate via data-based communications with at least one of said plurality of wireless subscriber devices.

14. (Currently amended) A method for providing wireless communication services to a plurality of wireless subscriber devices that are located in an aircraft, comprising:

generating, in an aircraft network located in said aircraft, radio frequency communication signals to communicate with at least one of said plurality of wireless subscriber devices that are located in said aircraft;

generating, in an air-to-ground network, radio frequency communications between said aircraft and a ground-based communications network system having at least one transceiver located on the ground; and

interconnecting said aircraft network and said air-to-ground network to establish communications between said plurality of wireless subscriber devices and said ground-based communications network by exchanging both subscriber traffic and at least one of network signaling and administrative data on separate concurrently available logical channels between said aircraft network means and said ground-based communications network.

15. (Original) The method for providing wireless communication services of claim 14 wherein said step of generating comprises:

establishing at least one cell site to communicate via communications with at least one of said plurality of wireless subscriber devices.

16. (Original) The method for providing wireless communication services of claim 15 wherein said step of establishing at least one cell site comprises:

operating at least one base station, each of which establishes a cell site to communicate via communications with at least one of said plurality of wireless subscriber devices.

17. (Original) The method for providing wireless communication services of claim 16 wherein said step of interconnecting comprises:

verifying the identity of said plurality of wireless subscriber devices.

18. (Original) The method for providing wireless communication services of claim 16 wherein said step of interconnecting comprises:

determining a set of services that each of said plurality of wireless communication devices is authorized to receive.

19. (Original) The method for providing wireless communication services of claim 16 wherein said step of generating, in an air-to-ground network, comprises:

emulating, in response to receipt of radio frequency communication signals from a one of said plurality of wireless subscriber devices, operation of said one wireless subscriber device in communicating with said ground-based communications system.

20. (Original) The method for providing wireless communication services of claim 16 wherein said step of generating, in an air-to-ground network, comprises:

generating downlink radio frequency signals for transmission to said at least one transceiver located on the ground;

receiving uplink radio frequency signals received from said at least one transceiver located on the ground; and

exchanging said downlink and uplink radio frequency signals with said at least one transceiver located on the ground.

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 6 of 32
219523v2

21. (Currently amended) The method for providing wireless communication services of claim 15 wherein said step of establishing at least one cell site comprises:

operating a plurality of base stations to communicate via communications with at least one of said plurality of wireless subscriber devices, ~~each~~ at least one of said plurality of base stations operating in a cellular technology that differs from those of the remaining ones of said plurality of base stations.

22. (Original) The method for providing wireless communication services of claim 21 wherein said step of interconnecting comprises:

converting the individual traffic and signaling channels received from said plurality of base stations to an aggregate data stream.

23. (Currently amended) The method for providing wireless communication services of claim 21 wherein said step of interconnecting comprises:

mobility management and hand over management for said aggregate data stream, comprising subscriber traffic from said plurality of wireless subscriber devices.

24. (Original) The method for providing wireless communication services of claim 22 wherein said step of interconnecting further comprises:

communicating via a plurality of ground-based base stations for communicating with at least one of said plurality of wireless subscriber devices; and

disaggregating said aggregate data stream by technology into a plurality of data streams and delivering each of said plurality of data streams to a corresponding one of said plurality of ground-based base stations.

25. (Original) The method for providing wireless communication services of claim 22 wherein said step of interconnecting further comprises:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 7 of 32
219523v2

interconnecting, via a plurality of mobile switching systems, said communications from at least one of said plurality of wireless subscriber devices with conventional Voice and Data switching systems.

26. (Original) The method for providing wireless communication services of claim 14 wherein said step of generating, in an aircraft network, comprises:

establishing at least one wireless LAN-based cell site to communicate via data-based communications with at least one of said plurality of wireless subscriber devices.

27. (Currently amended) A system for providing wireless communication services to a plurality of wireless subscriber devices that are located in an aircraft, comprising:

aircraft-based network means located in said aircraft for generating radio frequency communication signals to communicate with at least one of said plurality of wireless subscriber devices that are located in said aircraft;

ground-based network means for interconnecting said communications from at least one of said plurality of wireless subscriber devices with conventional Voice and Data switching systems; and

inner network means for interconnecting said aircraft-based network means and said ground-based network means to establish communications between said plurality of wireless subscriber devices and said conventional Voice and Data switching systems by exchanging both subscriber traffic and at least one of network signaling and administrative data on separate concurrently available logical channels between said aircraft network means and said ground-based communications network.

28. (Original) The system for providing wireless communication services of claim 27 wherein said aircraft-based network means comprises:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 8 of 32
219523v2

aircraft cellular communication means for establishing at least one cell site to communicate via communications with at least one of said plurality of wireless subscriber devices.

29. (Original) The system for providing wireless communication services of claim 28 wherein said aircraft cellular communication means comprises:

at least one base station means, each of which establishes a cell site to communicate via communications with at least one of said plurality of wireless subscriber devices.

30. (Original) The system for providing wireless communication services of claim 29 wherein said aircraft-based network means further comprises:

authentication means for verifying the identity of said plurality of wireless subscriber devices.

31. (Original) The system for providing wireless communication services of claim 29 wherein said aircraft-based network means further comprises:

authorization means for determining a set of services that each of said plurality of wireless communication devices is authorized to receive.

32. (Original) The system for providing wireless communication services of claim 29 wherein said inner network means comprises:

wireless subscriber device means, connected to said at least one base station means and responsive to receipt of radio frequency communication signals from a one of said plurality of wireless subscriber devices, for emulating operation of said one wireless subscriber device in communicating with said ground-based network means.

33. (Original) The system for providing wireless communication services of claim 32 wherein said air-to-ground network means comprises:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 9 of 32
219523v2

transmitter means for generating downlink radio frequency signals for transmission to said at least one transceiver located on the ground;

receiver means for receiving uplink radio frequency signals received from said at least one transceiver located on the ground; and

antenna means located on an external surface of said aircraft for exchanging said downlink and uplink radio frequency signals between said transmitter and said receiver means and said at least one transceiver located on the ground.

34. (Currently amended) The system for providing wireless communication services of claim 28 wherein said aircraft-based network means comprises:

a plurality of base station means to communicate via communications with at least one of said plurality of wireless subscriber devices, each at least one of said plurality of base station means operating in a cellular technology that differs from those of the remaining ones of said plurality of base station means.

35. (Original) The system for providing wireless communication services of claim 34 wherein said aircraft-based network means comprises:

data concentrator means for converting the individual traffic and signaling channels received from said plurality of base station means to an aggregate data stream.

36. (Currently amended) The system for providing wireless communication services of claim 35 wherein said ground-based network means comprises:

ground station controller means for mobility management and hand over management for said aggregate data stream, comprising subscriber traffic from said plurality of wireless subscriber devices.

37. (Currently amended) The system for providing wireless communication services of claim 35 wherein said ground-based network means further comprises:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 10 of 32
219523v2

a plurality of ground-based base station means for communicating with at least one of said plurality of wireless subscriber devices; and

data router disaggregator means for disaggregating said aggregate data stream by technology into a plurality of data streams and delivering each of said plurality of data streams to a corresponding one of said plurality of ground-based base station means.

38. (Original) The system for providing wireless communication services of claim 35 wherein said ground-based network means further comprises:

a plurality of mobile switching system means for interconnecting said communications from at least one of said plurality of wireless subscriber devices with conventional Voice and Data switching systems.

39. (Original) The system for providing wireless communication services of claim 27 wherein said aircraft-based network means comprises:

aircraft cellular communication means for establishing at least one wireless LAN-based cell site to communicate via data-based communications with at least one of said plurality of wireless subscriber devices.

40. (New) A system for providing wireless communication services to a plurality of wireless subscriber devices that are located in an aircraft, comprising:

aircraft network means located in said aircraft for generating radio frequency communication signals to communicate with at least one of said plurality of wireless subscriber devices that are located in said aircraft, comprising:

aircraft cellular communication means for establishing at least one cell site to communicate via communications with at least one of said plurality of wireless subscriber devices, comprising a plurality of base station means to communicate via communications with at least one of said plurality of wireless subscriber devices, said plurality of base station means operating in at least two different cellular technologies;

air-to-ground network means for radio frequency communications between said aircraft and a plurality of ground-based communications networks having at least one transceiver located on the ground;

aircraft interface means for interconnecting said aircraft network means and said air-to-ground network means to establish communications between said plurality of wireless subscriber devices and said plurality of ground-based communications networks, comprising:

data concentrator means for converting the subscriber traffic and signaling channels received from said plurality of base station means to an aggregate data stream;

wherein said air-to ground network means comprises:

data disaggregator means for disaggregating said aggregate data stream by technology into a plurality of data streams and delivering each of said plurality of data streams to a corresponding one of said plurality of ground-based communications networks.

41. (New) A method for providing wireless communication services to a plurality of wireless subscriber devices that are located in an aircraft, comprising:

generating, in an aircraft network located in said aircraft, radio frequency communication signals to communicate with at least one of said plurality of wireless subscriber devices that are located in said aircraft, comprising:

establishing at least one cell site to communicate via communications with at least one of said plurality of wireless subscriber devices comprising operating a plurality of base stations to communicate via communications with at least one of said plurality of wireless subscriber devices, said plurality of base stations operating in at least two different cellular technologies;

generating, in an air-to-ground network, radio frequency communications between said plurality of wireless subscriber devices and a plurality of ground-based communications networks having at least one transceiver located on the ground;

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 12 of 32

219523v2

interconnecting said aircraft network and said air-to-ground network to establish communications between said plurality of wireless subscriber devices and said plurality of ground-based communications networks, comprising:

converting the subscriber traffic and signaling channels received from said plurality of base stations to an aggregate data stream;

wherein said step of generating radio frequency communications between said plurality of wireless subscriber devices and a plurality of ground-based communications networks further comprises:

disaggregating said aggregate data stream by technology into a plurality of data streams and delivering each of said plurality of data streams to a corresponding one of said plurality of ground-based communications networks.

42. (New) A system for providing wireless communication services to a plurality of wireless subscriber devices that are located in an aircraft, comprising:

aircraft-based network means located in said aircraft for generating radio frequency communication signals to communicate with at least one of said plurality of wireless subscriber devices that are located in said aircraft, comprising:

data concentrator means for converting the individual traffic and signaling channels received from said plurality of base station means to an aggregate data stream comprising a plurality of base station means to communicate via communications with at least one of said plurality of wireless subscriber devices, said plurality of base station means operating in at least two different cellular technologies;

ground-based network means for interconnecting said communications from at least one of said plurality of wireless subscriber devices with conventional Voice and Data switching systems;

inner network means for interconnecting said aircraft-based network means and said ground-based network means to establish communications between said plurality of

wireless subscriber devices and said conventional Voice and Data switching systems, comprising:

data disaggregator means for disaggregating said aggregate data stream by technology into a plurality of data streams and delivering each of said plurality of data streams to a corresponding one of said plurality of conventional Voice and Data switching systems.

43. (New) The system for providing wireless communication services of claim 3 wherein said air-to-ground network means comprises:

transmitter means for generating downlink radio frequency signals for transmission to said at least one transceiver located on the ground via at least one satellite;

receiver means for receiving uplink radio frequency signals received from said at least one satellite; and

antenna means located on an external surface of said aircraft for exchanging said downlink and uplink radio frequency signals between said transmitter and said receiver means and said at least one satellite.

44. (New) The system for providing wireless communication services of claim 1 wherein said aircraft interface means comprises:

radio frequency management means for managing at least one radio frequency attribute of said system for providing wireless communication services from the set of radio frequency attributes including: the in-cabin radio frequency environment which controls wireless subscriber device access to services; the EMI/RFI environment by commanding the wireless subscriber devices to the lowest necessary radio frequency power; and a radio frequency scheme for signaling and traffic which does not cause interference to operations in the ground-based communication network.

45. (New) The system for providing wireless communication services of claim 1 wherein said aircraft interface means comprises:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 14 of 32
219523v2

in-cabin call termination means for providing a signaling termination for each call from a one of said wireless subscriber devices that are located in the aircraft to provide protocol management of signaling to both said ground-based communications network and said wireless subscriber devices.

46. (New) The system for providing wireless communication services of claim 45 wherein said in-cabin call termination means comprises:

first aircraft interface channel means for providing a radio frequency interface to the wireless subscriber devices to provide a pseudo base station with transparent handset signaling, to mimic the operation of the ground-based base station means to the wireless subscriber devices; and

second aircraft interface channel means for providing a radio frequency interface to the ground-based base station means to provide mirrored handset signaling to mimic the operation of the wireless subscriber devices to the ground-based base station means.

47. (New) The system for providing wireless communication services of claim 45 wherein said in-cabin call termination means comprises:

spoofing means for spoofing the wireless subscriber devices by intelligently removing and replacing selected network signaling information in the protocol management.

48. (New) The system for providing wireless communication services of claim 1 wherein said aircraft interface means comprises:

in-cabin call disabling means for disabling operation of selected ones of said wireless subscriber devices that are located in the aircraft.

49. (New) The system for providing wireless communication services of claim 1 wherein said aircraft interface means comprises:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 15 of 32
2195Z1v2

data concentrator means for converting the subscriber traffic and signaling channels received from said plurality of wireless subscriber devices to an aggregate data stream.

50. (New) The system for providing wireless communication services of claim 49 wherein said air-to-ground network means comprises:

data disaggregator means for converting the aggregate data stream received from said aircraft interface means into subscriber traffic and signaling channels for said ground-based communications network.

51. (New) The system for providing wireless communication services of claim 1 wherein said air-to-ground network means comprises:

data concentrator means for converting the subscriber traffic and signaling channels received from said ground-based communications network to an aggregate data stream.

52. (New) The system for providing wireless communication services of claim 51 wherein said aircraft interface means comprises:

data disaggregator means for converting the aggregate data stream received from said air-to-ground network means into subscriber traffic and signaling channels for said plurality of wireless subscriber devices.

53. (New) The system for providing wireless communication services of claim 49 further comprising:

wherein said aircraft interface means further comprises:

call management means for maintaining call data relating to said wireless subscriber devices that are generating said subscriber traffic and signaling channels;

wherein said air-to-ground network means further comprises:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 16 of 32
219523v2

a plurality of ground-based base station means for communicating with at least one of said plurality of wireless subscriber devices via said aggregate data stream; and

handoff management means, responsive to initiation of a call handoff from a first one of said ground-based base station means to a second one of said ground-based base station means, for redirecting transmission of said aggregate data stream from said first ground-based base station means to said second ground-based base station means.

54. (New) The system for providing wireless communication services of claim 49 wherein said aircraft interface means further comprises:

call management data handoff means for forwarding said call data, relating to said wireless subscriber devices that are generating said subscriber traffic and signaling channels, to said second ground-based base station means.

55. (New) The system for providing wireless communication services of claim 16 wherein said step of generating radio frequency communications between said aircraft and a ground-based communications network comprises:

generating downlink radio frequency signals for transmission by a transmitter located in said aircraft to said at least one satellite;

receiving uplink radio frequency signals from said at least one satellite in a receiver located in said aircraft; and

exchanging via an antenna located on an external surface of said aircraft said downlink and uplink radio frequency signals between said transmitter and said receiver and said at least one satellite.

56. (New) The method for providing wireless communication services of claim 14 wherein said step of interconnecting comprises:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 17 of 32
219523v2

managing at least one radio frequency attribute of said system for providing wireless communication services from the set of radio frequency attributes including: the in-cabin radio frequency environment which controls wireless subscriber device access to services; the EMI/RFI environment by commanding the wireless subscriber devices to the lowest necessary radio frequency power; and a radio frequency scheme for signaling and traffic which does not cause interference to operations in the ground-based communication network.

57. (New) The method for providing wireless communication services of claim 14 wherein said step of interconnecting comprises:

providing a signaling termination for each call from a one of said wireless subscriber devices that are located in the aircraft to provide protocol management of signaling to both said ground-based communications network and said wireless subscriber devices.

58. (New) The method for providing wireless communication services of claim 57 wherein said step of providing a signaling termination comprises:

providing a first radio frequency interface to the wireless subscriber devices to provide a pseudo base station with transparent handset signaling, to mimic the operation of the ground-based communications network to the wireless subscriber devices; and

providing a second radio frequency interface to the ground-based communications network to provide mirrored handset signaling to mimic the operation of the wireless subscriber devices to the ground-based communications network.

59. (New) The system for providing wireless communication services of claim 57 wherein said step of providing a signaling termination comprises:

spoofing the wireless subscriber devices by intelligently removing and replacing selected network signaling information in the protocol management.

60. (New) The system for providing wireless communication services of claim 14 wherein said step of interconnecting comprises:

disabling operation of selected ones of said wireless subscriber devices that are located in the aircraft.

61. (New) The system for providing wireless communication services of claim 14 wherein said step of interconnecting comprises:

converting the subscriber traffic and signaling channels received from said plurality of wireless subscriber devices to an aggregate data stream.

62. (New) The system for providing wireless communication services of claim 61 wherein said step of generating comprises:

data disaggregator means for converting the aggregate data stream received from said aircraft into subscriber traffic and signaling channels for said ground-based communications network.

63. (New) The system for providing wireless communication services of claim 14 wherein said step of generating comprises:

converting the subscriber traffic and signaling channels received from said ground-based communications network to an aggregate data stream.

64. (New) The system for providing wireless communication services of claim 63 wherein said step of interconnecting comprises:

converting the aggregate data stream received from said air-to-ground network means into subscriber traffic and signaling channels for said plurality of wireless subscriber devices.

65. (New) The method for providing wireless communication services of claim 64 further comprising:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 19 of 32
219523v2

wherein said step of generating further comprises:

maintaining call data relating to said wireless subscriber devices that are generating said subscriber traffic and signaling channels;

wherein said step of interconnecting further comprises:

communicating via a plurality of base stations with at least one of said plurality of wireless subscriber devices via said aggregate data stream; and
redirecting, in response to initiation of a call handoff from a first one of said ground-based base stations to a second one of said ground-based base stations, transmission of said aggregate data stream from said first ground-based base stations to said second ground-based base stations.

66. (New) The method for providing wireless communication services of claim 65 wherein said step of interconnecting further comprises:

forwarding said call data, relating to said wireless subscriber devices that are generating said subscriber traffic and signaling channels, to said second ground-based base station.

67. (New) The system for providing wireless communication services of claim 29 wherein said inner network means comprises:

transmitter means for generating downlink radio frequency signals for transmission to said at least one transceiver located on the ground via at least one satellite;

receiver means for receiving uplink radio frequency signals received from said at least one satellite; and

antenna means located on an external surface of said aircraft for exchanging said downlink and uplink radio frequency signals between said transmitter and said receiver means and said at least one satellite.

68. (New) The system for providing wireless communication services of claim 27 wherein said inner network means comprises:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 20 of 32
219523v2

radio frequency management means for managing at least one radio frequency attribute of said system for providing wireless communication services from the set of radio frequency attributes including: the in-cabin radio frequency environment which controls wireless subscriber device access to services; the EMI/RFI environment by commanding the wireless subscriber devices to the lowest necessary radio frequency power; and a radio frequency scheme for signaling and traffic which does not cause interference to operations in the ground-based communication network.

69. (New) The system for providing wireless communication services of claim 27 wherein said inner network means comprises:

in-cabin call termination means for providing a signaling termination for each call from a one of said wireless subscriber devices that are located in the aircraft to provide protocol management of signaling to both said ground-based communications network and said wireless subscriber devices.

70. (New) The system for providing wireless communication services of claim 69 wherein said in-cabin call termination means comprises:

first aircraft interface channel means for providing a radio frequency interface to the wireless subscriber devices to provide a pseudo base station with transparent handset signaling, to mimic the operation of the ground-based communications network to the wireless subscriber devices; and

second aircraft interface channel means for providing a radio frequency interface to the ground-based base station means to provide mirrored handset signaling to mimic the operation of the wireless subscriber devices to the ground-based communications network.

71. (New) The system for providing wireless communication services of claim 69 wherein said in-cabin call termination means comprises:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 21 of 32
219523v2

spoofing means for spoofing the wireless subscriber devices by intelligently removing and replacing selected network signaling information in the protocol management.

72. (New) The system for providing wireless communication services of claim 27 wherein said inner network means comprises:

in-cabin call disabling means for disabling operation of selected ones of said wireless subscriber devices that are located in the aircraft.

73. (New) The system for providing wireless communication services of claim 27 wherein said inner network means comprises:

data concentrator means for converting the subscriber traffic and signaling channels received from said plurality of wireless subscriber devices to an aggregate data stream.

74. (New) The system for providing wireless communication services of claim 73 wherein said air-to-ground network means further comprises:

data disaggregator means for converting the aggregate data stream received from said aircraft interface means into subscriber traffic and signaling channels for said ground-based communications network.

75. (New) The system for providing wireless communication services of claim 27 wherein said air-to-ground network means comprises:

data concentrator means for converting the subscriber traffic and signaling channels received from said ground-based communications network to an aggregate data stream.

76. (New) The system for providing wireless communication services of claim 75 wherein said inner network means comprises:

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 22 of 32
219523v2

data disaggregator means for converting the aggregate data stream received from said air-to-ground network means into subscriber traffic and signaling channels for said plurality of wireless subscriber devices.

77. (New) The system for providing wireless communication services of claim 75 further comprising:

wherein said ground-based network means further comprises:

call management means for maintaining call data relating to said wireless subscriber devices that are generating said individual traffic and signaling channels;

wherein said inner network means further comprises:

a plurality of ground-based base station means for communicating with at least one of said plurality of wireless subscriber devices via said aggregate data stream; and

handoff management means, responsive to initiation of a call handoff from a first one of said ground-based base station means to a second one of said ground-based base station means, for redirecting transmission of said aggregate data stream from said first ground-based base station means to said second ground-based base station means.

78. (New) The system for providing wireless communication services of claim 75 wherein said inner network means further comprises:

call management data handoff means for forwarding said call data, relating to said wireless subscriber devices that are generating said subscriber traffic and signaling channels, to said second ground-based base station means.

Serial No. 10/730,329
Amendment And Remarks Responsive To
Office Action Mailed 05/18/05
Page 23 of 32
219523v2